

Search Results

International Conference on Systems, Energy & Environment (ICSEE) 2022

ICSEE 2022 | International conference AUGUST 2022 | on systems energy and environment

5th & 6th August 2022 | GCE Kannur, Kerala, India

[Link to this page](#) | [Subscribe to this eJournal](#) (requires login)

Sort By
Title A-Z 

Displaying 1-1 of 1 papers



[Analysis of Pile Deformation Under Multylayered Liquefied Soil Using Static Equivalent Model](#)

Downloads
15

Proceedings of the International Conference on Systems, Energy and Environment 2022 (ICSEE 2022)

Number of pages: 5 • Posted 07 Dec 2022

Working Paper Series

SAYANTAN DUTTA, AMIT KOTAL, ANINDITA PAN and PRANOY ROY

Dr. B. C. Roy Engineering College, Durgapur, Dr. B. C. Roy Engineering College, Durgapur, Dr. B. C. Roy Engineering College, Durgapur and Dr. B. C. Roy Engineering College, Durgapur

Analysis of Pile Deformation Under Multylayered Liquefied Soil Using Static Equivalent Model

Proceedings of the International Conference on Systems, Energy and Environment 2022 (ICSEE 2022)

5 Pages • Posted: 7 Dec 2022

SAYANTAN DUTTA

Dr. B. C. Roy Engineering College, Durgapur

AMIT KOTAL

Dr. B. C. Roy Engineering College, Durgapur

ANINDITA PAN

Dr. B. C. Roy Engineering College, Durgapur

PRANOY ROY

Dr. B. C. Roy Engineering College, Durgapur

Date Written: July 27, 2022

Abstract

This paper uses a simpler approach, i.e., static equivalent approach, to estimate the response of piles resting on liquefied soil. For this, the pile head response under a three-storey reinforced concrete frame structure founded on liquified soil which is sandwiched between two non-liquefied crust layers is investigated using a synthetic accelerogram. Liquefaction degrades the soil stiffness around the pile, increasing pile response. For the single-layered soil profile, the maximum pile head deflection increases 3.66 times of that when liquefaction does not occur. It is also estimated that a non-liquefied crust layer directly over a liquefied soil generates lateral load on the pile, which largens the pile head displacement and intensifies the damaging effect further in addition to axial load. It is estimated that maximum pile head displacement are almost 2 times of that of without crust layer.

Keywords: Static equivalent model, crust layer, SAP2000v14, Liquefaction, lateral spreading.

Suggested Citation:

DUTTA, SAYANTAN and KOTAL, AMIT and PAN, ANINDITA and ROY, PRANOY, Analysis of Pile Deformation Under Multylayered Liquefied Soil Using Static Equivalent Model (July 27, 2022). Proceedings of the International Conference on Systems, Energy and Environment 2022 (ICSEE 2022), Available at SSRN: <https://ssrn.com/abstract=4295872> or <http://dx.doi.org/10.2139/ssrn.4295872>

ANALYSIS OF PILE DEFORMATION UNDER MULTYLAYERED LIQUEFIED SOIL USING STATIC EQUIVALENT MODEL

Sayantana Dutta
Department of Civil Engineering,
Dr. B. C. Roy Engineering College,
Durgapur, India
sayantandutta29@gmail.com

Amit Kotal
Department of Civil Engineering,
Dr. B. C. Roy Engineering College,
Durgapur, India
amit.kotal18@gmail.com

Anindita Pan
Department of Civil Engineering,
Dr. B. C. Roy Engineering College,
Durgapur, India
aninditapan.civil@gmail.com

Pranoy Roy
Department of Civil Engineering,
Dr. B. C. Roy Engineering College,
Durgapur, India
pranoyroy.dgp@gmail.com

Abstract— This paper uses a simpler approach, i.e., static equivalent approach, to estimate the response of piles resting on liquefied soil. For this, the pile head response under a three-storey reinforced concrete frame structure founded on liquefied soil which is sandwiched between two non-liquefied crust layers is investigated using a synthetic accelerogram. Liquefaction degrades the soil stiffness around the pile, increasing pile response. For the single-layered soil profile, the maximum pile head deflection increases 3.66 times of that when liquefaction does not occur. It is also estimated that a non-liquefied crust layer directly over a liquefied soil generates lateral load on the pile, which largens the pile head displacement and intensifies the damaging effect further in addition to axial load. It is estimated that maximum pile head displacement are almost 2 times of that of without crust layer.

Keywords— *Static equivalent model, crust layer, SAP2000v14, Liquefaction, lateral spreading.*

I. INTRODUCTION

Seismically well-designed structures fail during earthquakes due to the abrupt change of soil conditions due to earthquake-induced liquefaction and lateral spreading. The failure of structures often occurs due to excessive deformation of piles which are generally used under large buildings and bridges to carry a substantial axial load [1]. During a possible earthquake, the piles and surrounding soil are subjected to dynamic loads. Simultaneously, there is a significant reduction of soil strength and stiffness due to the non-linear behaviour of soil and pore water pressure generation. Due to excessive pore water pressure soil behaves as liquid with no shear strength and starts flowing laterally. If there is some inclination at the surface of the liquefied soil layer, then the flow is excessive. This phenomenon is called the lateral spreading of soil. The resistance to lateral deformation of a pile is significant in shallow depths as the deformation of laterally loaded piles near the ground surface is generally higher. This is because liquefaction potential at a greater depth is higher than shallow depth due to higher overburden pressure [2-5] at greater depth.

Though the results obtained from all these previous studies closely match the field case histories, experimental studies require a large laboratory setup. For this, some researchers introduced numerical formulations and modeling to analyse pile foundations [6-11]. Use of different computer software in

the numerical analysis of pile foundations in liquefiable soil, is increasing through the past decades.

Piles in liquefied soil sandwiched between the non-liquefied crust layer and the base layer at the bottom [12, 13] experience additional stresses due to the lateral movement of the non-liquefied crust above the liquefied layer. Dutta and Nanda [14] made an attempt to evaluate the pile response in liquefied soil sandwiched under non-liquefied crust layer. They found that the effect of crust layer has a significant role on soil-pile interaction. During the lateral spread, the upper non-liquefied crust layer is displaced laterally along with the underlying liquefied soil leading to further enhancement of lateral displacement and lateral force from the surface crust layer.

The above studies show that the seismic response of structures with deep foundations in layered soil are significantly affected by soil-pile interaction and this interaction is more complex in the presence of liquefied soils. Pile response analysis due to liquefaction required a large laboratory equipment setup or can be accurately predicted numerically. In this paper, a simpler approach for design engineers, i.e., static equivalent approach [15] is used to estimate the response of piles resting on liquefied soil and liquefied soil sandwiched between non-liquefied crust layers. Pile response is predicted using a synthetic accelerogram for maximum considered earthquake in the most severe Indian seismic zone (ISZ-V). Method accuracy was demonstrated by comparing the experimental observation reported by Zahmatkesh, 2019 [16], where a scaled accelerogram of Kobe earthquake is used.

II. STATIC EQUIVALENT APPROACH TO EVALUATE PILE RESPONSE

In static equivalent approach to assess dynamic response in pile foundation, first, the effect of dynamic forces (vibration) on the soil is evaluated in terms of free field motion. Then, the motion is converted to the stiffness of soil to model the soil as grounded spring with equivalent spring stiffness which is applied on the pile equivalently, considering soil dragging effect.

The pile and soil-pile interaction are modeled using SAP2000v14 [17] software, considering soil as a spring