

2022 International Conference on Intelligent Controller and Computing for Smart Power (ICICCCSP 2022)

**Hyderabad, India
21-23 July 2022**

Pages 1-542



**IEEE Catalog Number: CFP22AD7-POD
ISBN: 978-1-6654-7259-3**

**Copyright © 2022 by the Institute of Electrical and Electronics Engineers, Inc.
All Rights Reserved**

Copyright and Reprint Permissions: Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

For other copying, reprint or republication permission, write to IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, Piscataway, NJ 08854. All rights reserved.

****** This is a print representation of what appears in the IEEE Digital Library. Some format issues inherent in the e-media version may also appear in this print version.***

IEEE Catalog Number:	CFP22AD7-POD
ISBN (Print-On-Demand):	978-1-6654-7259-3
ISBN (Online):	978-1-6654-7258-6

Additional Copies of This Publication Are Available From:

Curran Associates, Inc
57 Morehouse Lane
Red Hook, NY 12571 USA
Phone: (845) 758-0400
Fax: (845) 758-2633
E-mail: curran@proceedings.com
Web: www.proceedings.com

CURRAN ASSOCIATES INC.
proceedings
.com

Autonomous Power Management for Hybrid AC/DC Nano Grid Using ESS and DG	271
<i>Syed Abdul Razzaq, Vairavasamy Jayasankar</i>	
Modeling and Analysis of MPPT Based Solar PV System Under Dynamic Weather Conditions	277
<i>Snehashis Ghoshal, Sumit Banerjee, Souvik Kundu, Debojyoti Biswas, Ashish Kumar Dayal, Chandan Kumar Chanda</i>	
Modeling and Performance Analysis of a Closed Loop PEMFC in Small Scale Stand Alone DC System	283
<i>Snehashis Ghoshal, Sumit Banerjee, Sweta, Rakesh Maji, Nehal Akhter, Chandan Kumar Chanda</i>	
Performance Analysis of a DFIG Based Wind Turbine with BESS System for Voltage and Frequency Stability During Grid Fault	289
<i>Ankur Adhikary, Niloy Goswami, Kaushik Barua, Ratul Dey, Arindam Barman, Mehedi Azad Shawon</i>	
Performance Analysis of Optimal AGC Regulator for Interconnected Power System Under Restructured Environment	295
<i>Ram Naresh Mishra</i>	
Power Grid Parameter Estimation Using Sparse Identification of Nonlinear Dynamics	301
<i>Asif Hamid, Danish Rafiq, Shahkar Ahmad Nahvi, Mohammad Abid Bazaz</i>	
Islanding Detection in Grid Based System Using Clarke Transformation	307
<i>Nenavath Suresh Rathod, Jitendra Kumar</i>	
Optimal Operation of Grid-Tied PV & BESS Powered Smart Home with Electric Vehicle Using AOA	312
<i>Sigma Ray, Kumari Kasturi, Manas Ranjan Nayak</i>	
Capacity Estimation of Lithium-Ion Battery with Least Squares Methods	318
<i>Shivanshu Kumar, Himadri Sekhar Bhattacharyya, Amalendu Bikash Choudhury, Chandan Kumar Chanda</i>	
A Fast Battery Charging Scheme for a Solar Energy System Using Intelligent Bi-Directional Converter	324
<i>Arpita Basu, Madhu Singh</i>	
Design of Smart Grid and Monitoring System Using IoT	330
<i>Priyanka Sen, Vandana Jha, Akshaya Aditya Abinash, Sharda Prasad Das, Subhadarsi Srimat</i>	
Combined ALFC-AVR Control of Diverse Energy Source Based Interconnected Power System Using Cascade Controller	335
<i>Biswanath Dekaraja, Lalit Chandra Saikia, Satish Kumar Ramoji</i>	
Single-Phase UPC with Lithium-Ion Battery System	341
<i>Nishant Patnaik, Sri Vamsi Deevi, Sai Teja Varma Lakkarsu, Sri Sai Venkat Nizampatnam</i>	
Intelligent Control Based Level Shifted PWM Multilevel Inverter	347
<i>Neelakantha Guru, Abinash Prusty, Siddhanta Pani, Kausik Nanda, Ajit Kumar Barisal</i>	
Compensator Design for Magnetic Levitation System	353
<i>Mitesh B Astik, Shital D Bhatt, Minesh K Joshi, Paresh R Modha</i>	

Modeling and analysis of MPPT based solar PV system under dynamic weather conditions

Snehashis Ghoshal

Department of Electrical Engineering
Dr. B.C.Roy Engineering College
Durgapur, West Bengal, India
snehashis0007@gmail.com

Sumit Banerjee

Department of Electrical Engineering
Dr. B.C.Roy Engineering College
Durgapur, West Bengal, India
sumit_9999@rediffmail.com

Souvik Kundu

Department of Electrical Engineering
Dr. B.C.Roy Engineering College
Durgapur, West Bengal, India
ksouvik36@gmail.com

Debojyoti Biswas

Department of Electrical Engineering
Dr. B.C.Roy Engineering College
Durgapur, West Bengal, India
debojyotib015@gmail.com

Ashish Kumar Dayal

Department of Electrical Engineering
Dr. B.C.Roy Engineering College
Durgapur, West Bengal, India
ashishkr.dayal1999@gmail.com

Chandan Kumar Chanda

Department of Electrical Engineering
Indian Institute of Engineering Science
& Technology (IEST), Shibpur
Howrah, West Bengal, India
ckc_math@yahoo.com

Abstract— A solar photovoltaic system (PV) generate electricity through photo-electric effect through photo cell. In practice, the output from a solar cell is quite low and so required number of solar cells are arranged properly in series-parallel combination to obtain significant output forming a module. In present analysis performance of a PV system having resistive load was analyzed under dynamic weather condition. A power electronic interface is embedded in the system to achieve maximum power point tracking (MPPT). A controller is incorporated in the system to regulate the duty ratio of the power electronic interface. In present study, two different algorithms were applied in the controller namely: Hill Climbing algorithm and Incremental Conductance. A comparative analysis of the system was carried out with the controller actuated by the above-mentioned logics simultaneously. Although both the method provided satisfactory results, INC method provided better system response.

Keywords— Sustainability, Greenhouse gases (GHG), PV array, MPPT controller, P&O method, INC method, DC-DC converter

I. INTRODUCTION

Energy is the main constituent of keeping civilization thriving and alive. Economic growth and advances in science and technology require consumption of energy. Total energy in this universe is a fixed quantity and exists in different forms in nature. Energy resources can be classified into two parts: non-renewable and renewable. It is evident that fossil fuel-based resources are of finite nature and hence will not sustain in distant future [1] whereas renewable is abundant by nature. On the other hand, fossil fuel-based resources pollute environment as they emit greenhouse gases during consumption whereas renewable resources are eco-friendly in nature. However, we cannot sacrifice our economic growth and more and more energy consumption is pertinent in the coming era followed by the technological advancement [2-5]. Keeping in view these two contradictory aspects, an optimized mixture of energy is evident for an efficient system.

In between different forms of renewables, solar is the most promising one due to its steadiness, ease of implementation and cost effectiveness [6]. Solar power has two forms for extraction, namely photovoltaic and solar thermal. PV

generates electricity both in islanded mode as well as on grid connected mode with similar performance characteristic [7-8]. Extraction of maximum power from such a system has become a matter of great concern to the researchers since last few decades [9]. This issue can be tackled by several proposed methods like Perturb and Observe (P&O), Incremental Conductance (INC) etc. which helps in optimize a PV system in operation. In present study, a simulation based comparative performance analysis is carried out with different power electronic interfaces at variable insolation level at different temperatures in MATLAB/Simulink environment. The power converter is regulated by a MPPT controller. Two different algorithms (P&O and INC) were adopted in this controller and performance analysis of these two were compared. MPPT algorithm is of significant importance for the tracking of maximum power point and hence necessary to implement an efficient system. The results shows that both the algorithm works efficiently. However, INC provided comparatively better response.

II. SOLAR POWER SYSTEM

Solar cell is the most crucial part in a PV based system. It is treated as a constant current source providing electricity while on exposure to the sunlight of a particular wavelength range. In present analysis, single diode representation of solar PV cell was considered [10] as shown in fig. 1. MATLAB/Simulink package provide several techniques to implement a solar PV system such as physical block modelling, mathematical block modelling and embedded MATLAB programming. In present study, physical block modelling is used. As mentioned above solar PV is modelled as a constant source of current connected in parallel with the diode as evident in figure 1.