

2025 IEEE 1st International Conference on Smart and Sustainable Developments in Electrical Engineering (SSDEE)

28 February – 02 March, 2025

(Conference Record # 64538)

Co-Sponsored by



Technically Co-Sponsored by



Organised by

Department of Electrical Engineering

Indian Institute of Technology (Indian School of Mines), Dhanbad
Jharkhand, India

<https://www.iitism.ac.in/>

Effective Control of Speed and Regenerative Braking in Electric Vehicles Utilizing Fractional Order PI Controller

Publisher: IEEE [Cite This](#) [PDF](#)

Dola Sinha ; Sudipta Ghosh ; Saibal Majumdar ; Chandan Bandyopadhyay ; Sovan Bhattacharya [All Authors](#)

11
Full
Text Views



Back to Results

Need Full-Text
access to IEEE Xplore for your organization?

[CONTACT IEEE TO SUBSCRIBE >](#)

- Abstract**
- Document Sections
- I. Introduction
- II. Methodology
- III. Results and Discussions
- IV. Conclusion and Future Scope
- Authors
- Figures
- References
- Keywords
- Metrics

Abstract:
In the automotive industry, a significant application of the Proportional Integral (PI) controller is in electric motors, specifically Brushless Direct Current (BLDC) motors used in Electric Vehicles (EVs). The accuracy of speed regulation in BLDC motors, acclaimed for their effectiveness and dependability, is crucial for enhancing vehicle performance and ensuring energy efficiency. On the other hand, regenerative braking is also important for energy recovery during vehicle navigation. In this paper, fractional order PI controller (FOPI) is implemented for smooth and precise control of speed and energy recovery during regenerative braking. Conventional Ziegler-Nichols method is used to tune the gains of the controller and for better controlling λ value for fractional order PI is predicted using trial and error method over extensive simulations on Simulink environment. The simulation results show accurate control of speed by variation of desired speed from 1500 rpm to 2800 rpm with fast transient response and without any delay. Energy recovery has been implemented through regenerative braking and show the battery charging and reverse flow of current during deceleration and applied braking in the EV.

Published in: 2025 IEEE 1st International Conference on Smart and Sustainable Developments in Electrical Engineering (SSDEE)

Date of Conference: 28 February 2025 - 02 March 2025 **DOI:** 10.1109/SSDEE64538.2025.10968516

Date Added to IEEE Xplore: 25 April 2025 **Publisher:** IEEE

▼ ISBN Information: **Conference Location:** Dhanbad, India

Electronic ISBN:979-8-3315-4210-8
Print on Demand(PoD) ISBN:979-8-3315-4211-5

I. Introduction
Electric vehicles (EVs) have been developed to meet societal needs, thanks to technological advancements. There will be reduced pollution and a reduced likelihood of combustion engines in favour of electric vehicles, which is regarded as an urgent matter that is currently receiving a lot of attention. The accessibility of charging stations is a significant challenge for electric vehicles. For safety reasons, it is important to update the battery health status frequently, and the velocity control could use some work.

Authors ▼

More Like This

Charging load prediction method for expressway electric vehicles considering dynamic battery state-of-charge and user decision iEnergy
Published: 2024

An Adaptive Event-Triggered Distributed PID Control for State of Charge Balancing of Multiple Batteries Based Electric Vehicles 2022 IEEE Electrical Power and Energy Conference (EPEC)
Published: 2022

[Show More](#)

MACHINE LEARNING Predictive Analysis for Business Decisions
eLEARNING COURSE PROGRAM
[LEARN MORE](#)

Search within results

Download PDFs

Export

Email Selected Results

Dola Sinha x

Author

Select All

Sort By Sequence -

Affiliation

Effective Control of Speed and Regenerative Braking in Electric Vehicles Utilizing Fractional Order PI Controller

Dola Sinha; Sudipta Ghosh; Saibal Majumdar; Chandan Bandyopadhyay; Sovan Bhattacharya

Publication Year: 2025 , Page(s): 1 - 6

Abstract HTML PDF CC BY

Quick Links

Search for Upcoming Conferences

IEEE Publication Recommender

IEEE Author Center

Proceedings

The proceedings of this conference will be available for purchase through Curran Associates.

64538 - SSDEE, 2025 (PRT)

Print on Demand Purchase at Partner

IEEE

Get Published in the IEEE Transactions on Privacy



Learn More

IEEE CertifAIed™

Assessor Training

Education in AI Ethics



Effective Control of Speed and Regenerative Braking in Electric Vehicles Utilizing Fractional Order PI Controller

Dola Sinha

Department of Electrical Engg
Dr. B. C. Roy Engineering College,
Durgapur, India
Email: dola.sinha@gmail.com

Sudipta Ghosh

Department of Electrical Engg
Dr. B. C. Roy Engineering College,
Durgapur, India
Email: gsudipta1000@gmail.com

Saibal Majumdar

Department of CSE(DS)
Dr. B. C. Roy Engineering College,
Durgapur, India
Email:
saibal.majumder.1729@gmail.com

Chandan Bandyopadhyay
Department of CSE(DS)

Dr. B. C. Roy Engineering College,
Durgapur, India
Email: chandanb.iest@gmail.com

Sovan Bhattacharya

Department of CSE(DS)
Dr. B. C. Roy Engineering College,
Durgapur, India
Email: sovan.cse@gmail.com

Abstract— In the automotive industry, a significant application of the Proportional Integral (PI) controller is in electric motors, specifically Brushless Direct Current (BLDC) motors used in Electric Vehicles (EVs). The accuracy of speed regulation in BLDC motors, acclaimed for their effectiveness and dependability, is crucial for enhancing vehicle performance and ensuring energy efficiency. On the other hand, regenerative braking is also important for energy recovery during vehicle navigation. In this paper, fractional order PI controller (FOPI) is implemented for smooth and precise control of speed and energy recovery during regenerative braking. Conventional Ziegler-Nichols method is used to tune the gains of the controller and for better controlling λ value for fractional order PI is predicted using trial and error method over extensive simulations on Simulink environment. The simulation results show accurate control of speed by variation of desired speed from 1500 rpm to 2800 rpm with fast transient response and without any delay. Energy recovery has been implemented through regenerative braking and show the battery charging and reverse flow of current during deceleration and applied braking in the EV.

Keywords— *Electric Vehicles, BLDC motor, FOPI controller, Regenerative braking, Speed Control, Battery SOC*

I. INTRODUCTION

Electric vehicles (EVs) have been developed to meet societal needs, thanks to technological advancements. There will be reduced pollution and a reduced likelihood of combustion engines in favour of electric vehicles. This has led to it being regarded as an urgent matter that is currently receiving a lot of attention. The accessibility of charging stations is the main concern regarding electric vehicles. For safety reasons, it is important to update the battery health status frequently, and the velocity control could use some work.

Secondly, in order to decrease charging period and ease range anxiety, electric vehicles must have fast charging technology. Examine the process for fast charging EVs, which calls for routine tuning of the DC-DC converters. An optimized proportional-integral (PI) controller and a control module monitor the state of charge (SOC) of the battery pack [1, 2]. Isolating, unidirectional, and bidirectional chargers with safety features are some of the types of electric vehicle charging that are discussed in the article [3]. Take a look at

some complex charging concepts and setups, like the bidirectional isolated dual active bridge charger and the unidirectional full-bridge series resonant charger [4]. The amount of time it takes to charge is controlled by various electronic power converters. Interleaved DC-DC converter designs, Quasi Z sources, and multilayer inverters are becoming more popular for these schemes [5]. Electric vehicle charging infrastructure has been improved by battery swapping technology, which has reduced charging time [6]. Intelligent transportation systems are required by electric vehicle (EV) technology to monitor EV charging levels in smart cities, as stated in [7]. Addressing future charging challenges in the development of autonomous electric vehicles (EVs) can be achieved through the transmission of traffic data using V2V or V2G communication.

According to [8], one way to lower the costs of the electric vehicle (EV) subsystem is to use magnet-less motors instead of magnet motors. Magnet motors used in electric vehicles are either permanent magnet synchronous motors (PMSM) or high-efficiency brushless direct current (BLDC). It is vulnerable to demagnetization and expensive rare earth minerals [9]. The induction and switching reluctance motors of the future, which do not require magnets, make use of cheap materials. Troublesome issues with electric vehicle (EV) applications include torque ripple, noise in switching reluctance motors (SRM), and losses in induction motors (IM) [10].

It is possible for a Battery Management System (BMS) to run reliably and safely if it is well-designed. In addition, critical tasks that greatly impact the accuracy of State of Charge (SOC) include data updates, regulation of battery voltage balance, and defect identification. The SOC of a battery management system is taken into account, along with other important issues that have been recently assessed. In an internal combustion engine vehicle, the fuel gauge shows the amount of gas left in the tank, and in a similar vein, the State of Charge (SOC) of the battery controls this feature. An in-depth analysis of the charge states provides information about the battery's current and available performance and ensures the electric vehicle's safe and reliable operation. (11, 12). It is critical to monitor the SOC of the battery pack to avoid overcharging or undercharging it, which can damage the battery or reduce its performance. Voltage and current